

Elfin IS High Resolution Inkjet Printer





Parameters

Controller: 151*93*32mm (H*W*D) / 5.9*3.7*1.3 inch
Printhead: 175*52*33mm (H*W*D) / 6.9*2.0*1.3 inch
Chinese, English, Japanese, French, German, Spanish, Portuguese and
Russian
50~600DPI
Can be set in Series No, Carton No, Pallet No, etc
1~12.7mm
0-60 m/min (300 DPI) 0-30 m/min(600 DPI)
Can be set, auto-calculated or use external synchronizer
UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128,
PDF417, DATAMATRIX, QR
Production date, expiry date with several formats for option
5inch 800*480 resolution color LCD touch screen
Ethernet: support PC software communication protocol SDK.
2) USB2.0: Support U-Disk
3) DB15: For external devices like photocell, synchronizer or alarm kit.
Identify ink type automatically and use the best printing parameters
Original HP ink cartridge guaranteed
Automatic measuring system for ink consumption
Standard side printing, down printing bracket and anti-shock bracket,
users can install according to their needs
AC 100V-240V/50-60HZ, 30W (Dedicated AC adaptor)
CE, FCC



Controller and Printhead Separated

Separated type, suitable for different installation environment.



Online Edit

Edit directly on the 5 inch touch screen.



Economic and Practical

 A good printer for integration of various equipment.



Chinese Input

Support Chinese Input, in multiple fonts.